

The Heavy-Duty lubricator for serious tools boxes. Stays where you spray with polarized film.

Infinity RCL: All-purpose lubricating fluid can be used on sliding doors, hinges, bicycles, locks, sewing machines, air tools, etc.

DESIGNED FOR PERFORMANCE

- Specifically designed for thin film, heavy load lubrication applications
- Reduces friction and drag by forming a high strength boundary film
- Speeds up drilling and tapping; cutting edges remain sharper longer
- Prolongs operating life
- Resists rust and corrosion
- Displaces water, inhibiting oxidation (rust)
- Will not tarnish metals
- Designed to withstand corrosive environments
- Compatible with typical seals except EPDM
- Apply with a spray or a brush between rubbing surfaces

Product ID#	3500-350-1 (350g x 1) 3500-52-1 (52g x 1) 3500-52-12 (52g x 12)	3500-20-1 (20L Pail)
	3500-425-12 (425g x 12)	3500-205-1 (205L Drum)
	3500-4-4 (4L x 4)	

<u>TYPICAL PROPERTIES</u>	<u>ASTM METHOD</u>	<u>Needle Oiler</u>
Appearance		Clear, Dark, Amber
Colour	D 1500	2.3
Flash Point	D 92	130
Pour Point	D 97	-36
Fire Point	D 92	135
Viscosity @ 40°C (cSt)	D 445	8 cSt
Specific Gravity	D 445	0.860
Density @ 20°C	D 941	0.860 g/ml