

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Trade name : PWR4 Diesel AG

1.2. Recommended use and restrictions on use

Recommended use : Petrochemical, Fuel additives
Restrictions on use : No additional information available

1.3. Supplier

Supplier

Awsum Outcomes Inc
Bay 5, 409 38th Avenue NE
Calgary, Alberta, T2E 6R9
Canada
T 1 587-353-2000; Toll Free: 1-844-512-4093
sales@wvi.global - www.awsumoutcomes.com

1.4. Emergency telephone number

Emergency number : 1-844-512-4093 (8am to 5pm MST)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Carcinogenicity Category 1B	H350	May cause cancer
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Hazardous to the aquatic environment – Acute Hazard Category 1	H400	Very toxic to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 1	H410	Very toxic to aquatic life with long lasting effects
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazard statements (GHS CA)	: H226 - Flammable liquid and vapor H302 - Harmful if swallowed H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H350 - May cause cancer H361 - Suspected of damaging fertility or the unborn child H373 - May cause damage to organs through prolonged or repeated exposure H400 - Very toxic to aquatic life H410 - Very toxic to aquatic life with long lasting effects
Precautionary statements (GHS CA)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical, ventilating, lighting equipment. P242 - Use only non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe vapors. P261 - Avoid breathing vapors. P264 - Wash hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor. P330 - Rinse mouth. P331 - Do NOT induce vomiting. P302+P352 - IF ON SKIN: Wash with plenty of water. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P312 - Call a POISON CENTER, a doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see supplemental first aid instruction on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use water spray, foam, dry chemical powder, carbon dioxide (CO ₂) to extinguish. P391 - Collect spillage. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P235 - Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other hazards which do not result in classification	: When heated above 100 °C/212 °F may undergo a self-accelerating, exothermic reaction which causes a rapid rise in temperature and pressure. Rupture of storage vessels and fire should be anticipated in case of such temperature.
---	--

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.4. Unknown acute toxicity (GHS CA)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	% (w/w)
solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified, [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	CAS-No.: 64742-95-6	30 - 60
2-ethylhexyl nitrate	-	CAS-No.: 27247-96-7	15 - 40
1,2,4-trimethylbenzene	1,2,4-trimethylbenzene	CAS-No.: 95-63-6	10 - 30
mesitylene	mesitylene, 1,3,5-trimethylbenzene	CAS-No.: 108-67-8	5 - 10
(2-methoxymethylethoxy)propanol	-	CAS-No.: 34590-94-8	1 - 5
2-ethylhexan-1-ol	-	CAS-No.: 104-76-7	1 - 5
xylene	xylene	CAS-No.: 1330-20-7	1 - 5
cumene	cumene	CAS-No.: 98-82-8	1 - 5
1,2,3-trimethylbenzene	-	CAS-No.: 526-73-8	1 - 5
cymene	-	CAS-No.: 25155-15-1	0.1 - 1
methyl-1H-benzotriazole	-	CAS-No.: 29385-43-1	0.1 - 1

Comments

: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018
Proprietary HMIRA registration number: 3502293.
Exemption granted date: 10/2/2023

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Give oxygen or artificial respiration if necessary.

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention.

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, seek medical advice immediately and show this container or label. Rinse mouth out with water. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
First-aid measures general	: If medical advice is needed, have product container or label at hand. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation. Redness. Itching. Absorbed through the skin. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain. May result in aspiration into the lungs, causing chemical pneumonia.
Chronic symptoms	: May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
Most Important Symptoms/Effects	: reduced fetal weight, increase in fetal deaths, skeletal malformations.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically. Symptoms may be delayed. Keep under medical supervision for at least 48 hours.
-----------------------------------	---

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Alcohol-resistant foam. Carbon dioxide. Use extinguishing agent suitable for surrounding fire.
------------------------------	---

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Do not use a heavy water stream.
--------------------------------	------------------------------------

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Vapors may form explosive mixture with air. Heating may cause a fire or explosion.
Reactivity in case of fire	: When heated above 100 °C/212 °F may undergo a self-accelerating, exothermic reaction which causes a rapid rise in temperature and pressure. Rupture of storage vessels and fire should be anticipated in case of such temperature.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Nitrogen oxides.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate the danger area. Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Eliminate all ignition sources if safe to do so.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Remove ignition sources.

Methods for cleaning up : Caution : this product can cause the floor to be slippery. Move containers from spill area. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water. Prevent entry to sewers and public waters. Use non-sparking tools.

Other information : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation to minimize dust and/or vapor concentrations. Avoid breathing vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid contact during pregnancy and while nursing. Eliminate all ignition sources if safe to do so. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Take precautionary measures against static discharge. Use explosion-proof equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not re-use container for any purpose.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store in a dry place. Handle empty containers with care because residual vapors are flammable. Keep only in the original container. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Refer to Section 10 on Incompatible Materials. Store in accordance with local, regional, national or international regulation. Do not store in unlabelled containers.

Incompatible products : Strong oxidizing agents.

Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

1,2,4-trimethylbenzene (95-63-6)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	1,2,4-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	1,2,4-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	1,2,4-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	1,2,4-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
mesitylene (108-67-8)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	1,3,5-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	1,3,5-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	1,3,5-Trimethyl benzene
OEL TWA [ppm]	10 ppm

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

mesitylene (108-67-8)	
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	1,3,5-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023
(2-methoxymethylethoxy)propanol (34590-94-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy) propanol (Dipropylene glycol methyl ether, DPGME)
OEL TWA	606 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	909 mg/m ³
OEL STEL [ppm]	150 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Dipropylene glycolmonomethyl ether
VECD (OEL STEL)	909 mg/m ³
VECD (OEL STEL) [ppm]	150 ppm
VEMP (OEL TWA)	606 mg/m ³
VEMP (OEL TWA) [ppm]	100 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether [bis-(2-Methoxypropyl) ether (DPGME)]
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA [ppm]	50 ppm
Notations and remarks	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2023
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA [ppm]	50 ppm

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

(2-methoxymethylethoxy)propanol (34590-94-8)	
Notations and remarks	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2023
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA [ppm]	50 ppm
Notations and remarks	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2023
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)propanol (DPGME)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Notations and remarks	Skin
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA [ppm]	50 ppm
Notations and remarks	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2023
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Dipropylene glycol methyl ether (DPGME)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-ethylhexan-1-ol (104-76-7)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	2-Ethyl-1-hexanol
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT irr & eye irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	2-Ethyl-1-hexanol
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT irr & eye irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	2-Ethyl-1-hexanol
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT irr & eye irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	2-Ethyl-1-hexanol
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT irr & eye irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
xylene (1330-20-7)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Xylene, o, m & p isomers (Dimethylbenzene)
OEL TWA	434 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	651 mg/m ³
OEL STEL [ppm]	150 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Xylene (o-, m-, p- isomers) (Dimethylbenzene)
VECD (OEL STEL)	651 mg/m ³
VECD (OEL STEL) [ppm]	150 ppm
VEMP (OEL TWA)	434 mg/m ³
VEMP (OEL TWA) [ppm]	100 ppm

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

xylene (1330-20-7)	
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Xylene
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA [ppm]	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2023
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Xylene
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Notations and remarks	URT & eye irr; CNS impair
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA [ppm]	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2023
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA [ppm]	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2023
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Xylene (o, m-, p-isomers)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Xylene (o, m-, p-isomers)

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

xylene (1330-20-7)	
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Xylene (o, m & p isomers)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
OEL TWA [ppm]	20 ppm
Notations and remarks	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2023
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Xylene (o-, m-, p-isomers)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
1,2,3-trimethylbenzene (526-73-8)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	1,2,3-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	1,2,3-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	1,2,3-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

1,2,3-trimethylbenzene (526-73-8)	
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	1,2,3-Trimethyl benzene
OEL TWA [ppm]	10 ppm
Notations and remarks	TLV® Basis: CNS impair; hematologic eff
Regulatory reference	ACGIH 2023
cumene (98-82-8)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA	246 mg/m ³
OEL TWA [ppm]	50 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Cumene (Isopropylbenzene)
VEMP (OEL TWA)	246 mg/m ³
VEMP (OEL TWA) [ppm]	50 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	25 ppm
OEL STEL [ppm]	75 ppm
Notations and remarks	IARC group 2B carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT adenoma; neurological eff. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	50 ppm
Notations and remarks	Eye, skin, & URT irr; CNS impair
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT adenoma; neurological eff. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

cumene (98-82-8)	
Regulatory reference	ACGIH 2023
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT adenoma; neurological eff. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	74 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	74 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	50 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	5 ppm
Notations and remarks	TLV® Basis: URT adenoma; neurological eff. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Cumene
OEL TWA [ppm]	50 ppm
OEL STEL [ppm]	74 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
cymene (25155-15-1)	
Canada (Ontario) - Occupational Exposure Limits	
Local name	Cymene (sum of o-, m- and p-isomers)
OEL TWA	274 mg/m ³
OEL TWA [ppm]	50 ppm

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

cymene (25155-15-1)

Notations and remarks	Skin
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833

8.2. Appropriate engineering controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure exposure is below occupational exposure limits (where available). Handle in accordance with good industrial hygiene and safety procedures. Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Environmental exposure controls : Avoid release to the environment. Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

Hand protection:

Wear suitable gloves resistant to chemical penetration. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Selection of protective gloves should be made based on the type of task performed. Recommended materials. Nitrile rubber.
Breakthrough time : 30 minutes. Thickness ≥ 0.4 mm

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided. Safety footwear

Respiratory protection:

Where excessive vapor, mist, or dust may result, use approved respiratory protection equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Transparent.
Color	: amber
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 46 °C (114.8 °F; Pensky-Martens closed cup)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.9212
Density	: 0.92 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 6.1 mm ² /s (40 °C, 104 °F)
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: Flammable liquid and vapor. Can form explosive mixtures with air. Heating may cause a fire or explosion.
Chemical stability	: Unstable at temperatures greater than 100 °C/212 °F.
Possibility of hazardous reactions	: Hazardous polymerization: Will not occur.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating. Extremely high or low temperatures. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

PWR4 Diesel AG	
ATE CA (oral)	1428.571 mg/kg body weight
solvent naphtha (petroleum), light arom. (64742-95-6)	
LD50 oral rat	3492 mg/kg (female)
LD50 oral	6984 mg/kg (rat, male)
LD50 dermal rabbit	> 3160 mg/kg (OECD 402)
LC50 Inhalation - Rat (Vapours)	6193 mg/l/4h (OECD 403)
2-ethylhexyl nitrate (27247-96-7)	
LD50 oral rat	> 9600 mg/kg
LD50 dermal rabbit	> 4800 mg/kg
LC50 Inhalation - Rat	> 4.6 mg/l (1 h)
ATE CA (oral)	500 mg/kg body weight
ATE CA (Dermal)	1100 mg/kg body weight
ATE CA (dust,mist)	1.5 mg/l/4h

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

1,2,4-trimethylbenzene (95-63-6)	
LD50 oral rat	6000 mg/kg
LD50 dermal rabbit	> 3440 mg/kg (similar substance)
LC50 Inhalation - Rat (Vapours)	> 10200 mg/l/4h (similar substance)
ATE CA (Gases)	4500 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

mesitylene (108-67-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 3440 mg/kg (similar substance)
LC50 Inhalation - Rat (Vapours)	> 10.2 mg/l/4h (similar substance)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

xylene (1330-20-7)	
IARC group	3 - Not classifiable

cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

PWR4 Diesel AG	
Viscosity, kinematic	6.1 mm ² /s (40 °C, 104 °F)

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation. Redness. Itching. Absorbed through the skin. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain. May result in aspiration into the lungs, causing chemical pneumonia.
Most Important Symptoms/Effects	: reduced fetal weight, increase in fetal deaths, skeletal malformations.
Chronic symptoms	: May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.

solvent naphtha (petroleum), light arom. (64742-95-6)	
LC50 - Fish [1]	8.2 mg/l (96 h, Pimephales promelas, similar substance)
EC50 - Crustacea [1]	4.5 mg/l (48 h, Daphnia magna, similar substance)
EC50 72h - Algae [1]	3.1 mg/l (72 h, Pseudokirchneriella subcapitata)
NOEC chronic fish	2.6 mg/l (14 d, Pimephales promelas, similar substance)
NOEC chronic crustacea	0.4 mg/l (21 d, Daphnia magna, similar substance)
NOEC chronic algae	0.5 mg/l (72 h, Pseudokirchneriella subcapitata)
2-ethylhexyl nitrate (27247-96-7)	
LC50 - Fish [1]	2 mg/l (96 h, Danio rerio)
EC50 - Crustacea [1]	0.83 mg/l (48 h, Daphnia magna)
EC50 72h - Algae [1]	> 2.53 mg/l (72 h, Pseudokirchneriella subcapitata)
NOEC chronic algae	2.22 mg/l (72 h, Pseudokirchneriella subcapitata)
1,2,4-trimethylbenzene (95-63-6)	
LC50 - Fish [1]	7.72 mg/l (96 h, Pimephales promelas)
EC50 - Crustacea [1]	3.6 mg/l (48 h, Daphnia magna)
mesitylene (108-67-8)	
LC50 - Fish [1]	12.52 mg/l (96 h, Carassius auratus)
EC50 - Crustacea [1]	6 mg/l (48 h, Daphnia magna)
EC50 72h - Algae [1]	53 mg/l (48 h, Desmodesmus subspicatus)
NOEC chronic crustacea	0.4 mg/l (21 d, Daphnia magna)
NOEC chronic algae	16 mg/l (48 h, Desmodesmus subspicatus)

12.2. Persistence and degradability

PWR4 Diesel AG	
Persistence and degradability	Biodegradability in water: no data available.
2-ethylhexyl nitrate (27247-96-7)	
Biodegradation	0 % (28 d, OECD 310)

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

mesitylene (108-67-8)	
Biodegradation	42 % (28 d)

12.3. Bioaccumulative potential

PWR4 Diesel AG	
Bioaccumulative potential	No data available concerning bioaccumulation.

solvent naphtha (petroleum), light arom. (64742-95-6)	
BCF - Fish [1]	10 – 2500

2-ethylhexyl nitrate (27247-96-7)	
BCF - Fish [1]	1196
Partition coefficient n-octanol/water (Log Pow)	5.24

1,2,4-trimethylbenzene (95-63-6)	
BCF - Fish [1]	243
Partition coefficient n-octanol/water (Log Pow)	3.63

mesitylene (108-67-8)	
BCF - Fish [1]	3.42
Partition coefficient n-octanol/water (Log Pow)	161

12.4. Mobility in soil

PWR4 Diesel AG	
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not pierce or burn, even after use.
Additional information : Flammable vapors may accumulate in the container.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

14.1. UN number

UN-No. (TDG) : UN1993
DOT NA No : UN1993
UN-No. (IMDG) : 1993
UN-No. (IATA) : 1993

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.2. UN proper shipping name

Proper Shipping Name (TDG)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (DOT)	: Flammable liquids, n.o.s.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.

14.3. Transport hazard class(es)


TDG

Transport hazard class(es) (TDG)	: 3
Hazard labels (TDG)	: 3



DOT

Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3



14.4. Packing group

Packing group (TDG)	: III
Packing group (DOT)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III

14.5. Environmental hazards

Dangerous for the environment	: Yes
Marine pollutant	: Yes



Other information	: No supplementary information available.
-------------------	---

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.6. Special precautions for user

TDG

UN-No. (TDG)	: UN1993
TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS, 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan). SOR-2019-101
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L
Emergency Response Guide (ERG) Number	: 128

DOT

UN-No. (DOT)	: UN1993
DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG

Special provision (IMDG) : 223, 274, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : A

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provision (IATA) : A3
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

solvent naphtha (petroleum), light arom. (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

2-ethylhexyl nitrate (27247-96-7)

Listed on the Canadian DSL (Domestic Substances List)

1,2,4-trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List)

mesitylene (108-67-8)

Listed on the Canadian DSL (Domestic Substances List)

(2-methoxymethylethoxy)propanol (34590-94-8)

Listed on the Canadian DSL (Domestic Substances List)

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-ethylhexan-1-ol (104-76-7)

Listed on the Canadian DSL (Domestic Substances List)

xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

1,2,3-trimethylbenzene (526-73-8)

Listed on the Canadian DSL (Domestic Substances List)

cumene (98-82-8)

Listed on the Canadian DSL (Domestic Substances List)

cymene (25155-15-1)

Listed on the Canadian DSL (Domestic Substances List)

methyl-1H-benzotriazole (29385-43-1)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

PWR4 Diesel AG

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

solvent naphtha (petroleum), light arom. (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

2-ethylhexyl nitrate (27247-96-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

1,2,4-trimethylbenzene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

mesitylene (108-67-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

(2-methoxymethylethoxy)propanol (34590-94-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-ethylhexan-1-ol (104-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

1,2,3-trimethylbenzene (526-73-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

cumene (98-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

cymene (25155-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

methyl-1H-benzotriazole (29385-43-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Issue date : 08-10-2023

Data sources : Supplier's safety documents. ECHA (European Chemicals Agency).

Training advice : Training staff on good practice.

Full text of H-phrases:

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

PWR4 Diesel AG

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of H-phrases:

H410	Very toxic to aquatic life with long lasting effects
------	--

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.